





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A44B 1/32, 1/08, 7/00	A1	(11) International Publication Number: WO 99/11154 (43) International Publication Date: 11 March 1999 (11.03.99)
<p>(21) International Application Number: PCT/NL98/00488</p> <p>(22) International Filing Date: 31 August 1998 (31.08.98)</p> <p>(30) Priority Data: 1006906 1 September 1997 (01.09.97) NL</p> <p>(71)(72) Applicant and Inventor: RILEY, Hedley, Godfried [NL/NL]; Leksmondhof 52, NL-1108 EN Amsterdam (NL).</p> <p>(74) Agent: VAN KAN, J., J., H.; Algemeen Octrooibureau, World Trade Center, Pastoor Petersstraat 160, NL-5612 LV Eindhoven (NL).</p>	<p>(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. In English translation (filed in Dutch).</p>	

(54) Title: A BUTTON COMBINATION

(57) Abstract

A button combination comprising a base part to be attached to an article of clothing and a main part to be detachably connected to said base part (1). The main part (8) is provided with two disc-shaped portions (9, 9) extending parallel to each other, which disc-shaped portions are interconnected near their circumference (10) over part thereof. A recess (11) is provided in one of said disc-shaped portions, which recess is open at an edge of the disc-shaped portion in question. The base part (1) comprises two parallel disc-shaped portions (2, 3), which are interconnected by a connecting piece (5), all this in such a manner that in order to interconnect the base part and the main part, the connecting piece (5) of the base part is inserted into the recess in the main part with a clamped fit.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A button combination.

The invention relates to a button combination comprising a base part to be attached to an article of clothing and a main part to be detachably connected to said base part. Button combinations of this kind, which are for example used for interchangeably placing decorative buttons on the base part, are known from International patent application WO 96/05749 and European patent application no. 0 664 971.

With the button combination according to WO 96/05749, a conventional button is used as the base part, which button is provided with a few holes for passing yarn therethrough, by means of which yarn the button is fixed to an article of clothing in a usual manner. The main part to be placed on the base part, which forms a decorative button or the like, is provided with bar-shaped parts, which, in order to fix the main part to the base part, must be passed through the openings provided in the base part for passing the fixing yarn therethrough. The bar-shaped portions are thereby provided with barbs at their free ends, which barbs engage behind the base part when the main part is placed on the base part. When the main part is to be detached from the base part, the barbs engaging behind said base part must be moved towards each other. This is difficult, and generally it will only be possible if the base part is attached relatively loosely to the article of clothing by means of the fixing yarn, so that sufficient space is present between the side of a base part that faces an article of clothing and the article of clothing itself. When the base part is loosely attached in this manner, articles of clothing fitted with such a button combination will look slovenly, however.

With the construction according to European patent application no. 0 664 971, the base part is made up of a U-shaped element, which carries projecting arms at the free ends of its legs, which arms must be received in a circular groove formed in the main part, whereby the base part and the main part must be moved to a position in which they are fixed relative to each other by turning the two parts with respect to each other. The construction of the base part and the main part of this known construction is relatively complicated, whilst furthermore it is not possible to realise a firm attachment of the base part to the article of clothing so that the base part will take up a desired position relative to the article of clothing. Also with this construction, undesirable

rotation of the base part relative to the article of clothing will rather occur, which will make articles of clothing fitted with such button combinations look slovenly.

According to the invention, the main part is provided
5 with two disc-shaped portions extending parallel to each other, which disc-shaped portions are interconnected near their circumference over part thereof, wherein a recess is provided in one of said disc-shaped portions, which recess is open at an edge of the disc-shaped portion in question, whilst the base part comprises two parallel disc-shaped portions, which
10 are interconnected by a connecting piece, all this in such a manner that in order to interconnect the base part and the main part, the connecting piece of the base part is inserted into the recess in the main part with a clamped fit, wherein one of the disc-shaped portions of the base part is positioned between the disc-shaped portions of the main part.

15 When using the construction according to the invention, the base part can be firmly attached to the article of clothing, in such a manner that one of the disc-shaped portions of the base part butts against a respective panel of the article of clothing and is fixed thereto. The other disc-shaped portion can be passed through a respective buttonhole
20 when buttoning up the article of clothing in question. The disc-shaped portion that is passed through said buttonhole may be suitably shaped to conform to a large degree with conventional buttons used in shirts and the like, for example, so that the base part can also be used without using the main part, if desired. If it is desired to give the article of clothing
25 an additional touch of distinction, a desired main part can be placed on the base part by simply sliding the main part onto the base part, whereby a firm anchoring between the main part and the base part can be realised.

The invention will be explained in more detail with reference to the accompanying figures, which diagrammatically show an
30 embodiment of the button combination according to the invention.

Figure 1 is a perspective view of a base part of a button combination according to the invention.

Figure 2 is a smaller-scale side view of the base part shown in Figure 1.

35 Figure 3 is a perspective view of an embodiment of a main part for a button combination according to the invention.

Figure 4 is a smaller-scale plan view of Figure 3.

Figure 5 is a plan view of a box for storing main parts.

Figure 6 is a larger-scale, sectional view of Figure 5.

As is shown in Figures 1 and 2, a base part 1 comprises two parallel disc-shaped portions 2 and 3, whereby the upper portion 2 of the illustrated embodiment is slightly smaller than the lower portion 3, seen in sectional view.

The two disc-shaped portions 2 and 3 are interconnected by a connecting piece 4. Said connecting piece is comprised of a central portion 5 having a circular circumference and two diametrically opposed ribs 6 and 7 extending radially outwards from central portion 5, whose free ends are slightly rounded.

Disc-shaped portion 3 may be provided with a few holes (not shown) extending through the disc-shaped portion for passing a fixing yarn, by means of which base part 1 can be attached to a panel of an article of clothing or the like, in such a manner that disc-shaped portion 3 firmly butts against said panel of said article of clothing, whilst disc-shaped portion 2 can be passed through a corresponding buttonhole when using the article of clothing.

Another possibility is to form a (preferably) blind hole in the central portion 5 of the connecting piece, which, seen in Figure 1, extends a specified length from the underside of disc-shaped portion 3 through disc-shaped portion 3 and into central portion 5 of connecting piece 4. It is possible to insert into said hole the shank of a nail consisting of a shank and a head, in such a manner that a respective panel of an article of clothing or the like is clamped between the head of said nail and disc-shaped portion 3, whilst said shank is clampingly accommodated in the central portion 5 of connecting piece 4. Advantageous is the fact that several nails can be pressed into the respective base parts 1 simultaneously, for example by means of a simple set of press tools, so that a considerable amount of time is saved in comparison with conventional fixing operations.

Another possibility of providing the base parts is to glue the base parts to the article of clothing.

It will be apparent that a firm abutment of disc-shaped portion 3, and thus of base part 1, against a respective panel of an article of clothing can be ensured at all times, so that undesirable rotation or tilting of base part 3 with respect to the article of clothing

will be avoided.

In particular when using the above-described nails, the risk of base parts becoming detached is practically excluded.

Disc-shaped portion 2 can be efficiently configured to have the shape of a simple button, for example buttons used on shirts or the like, setting aside the fact that disc-shaped portion 2 will not comprise the usual holes for the passage of a fixing yarn in that case. By configuring disc-shaped portion 2 to have such a shape resembling a conventional button, the base part can be used by itself.

In order to give the article of clothing an additional touch of distinction, the base part may be used in combination with a main part as shown diagrammatically in Figures 3 and 4.

As is shown in said figures, main part 8 comprises two disc-shaped portions 9 and 9' extending parallel to each other, and which are interconnected by a connecting rib 10, which is disposed near the circumference of said disc-shaped portions 9 and 9' and which extends over part of the circumference of said disc-shaped portions. A recess 11 is provided in disc-shaped portion 9, which recess 11 is open near one end of disc-shaped portion 9. Recess 11 is thereby bounded by two boundary surfaces 12 and 13, which extend obliquely towards each other from the outer circumference of disc-shaped portion 9. Near their ends remote from the circumferential edge of disc-shaped portion 9, boundary surfaces 12 and 13 blend into two curved boundary surfaces 14 and 15, which form a connection between boundary surfaces 12 and 13 and two parallel boundary surfaces 16 and 17 of recess 11.

Main part 8 of the button combination according to the invention can now be slid over base part 1, in such a manner that disc-shaped portion 2 of base part 1 will be positioned between disc-shaped portions 9 and 9' of main part 8. The connecting piece 4 of base part 1 will thereby be slid into recess 11, with rib 6 or rib 7 positioned in front. Said insertion of connecting piece 4 is facilitated by the funnel-shaped entry of recess 11. When main part 8 is slid completely over base part 1, the central portion 5 of connecting piece 4 will be positioned in that part of recess 11 which is bounded by boundary surfaces 14 and 15, whilst rib 6 or rib 7 will be positioned in that part of recess 11 which is bounded by boundary surfaces 16 and 17.

Main part 8 is thereby locked against rotation with respect to the base part, whilst some deformation of portion 5 of connecting piece 4 and/or of boundary surfaces 12, 13 of recess 11 must take place before inserting central portion 5 into the part of recess 11 that is bounded by boundary surfaces 14 and 15, so that connecting piece 4 will be accommodated in recess 11 with a clamped fit, and main part 8 can only be removed from base part 1 by exerting a specific force.

When main part 8 is present on base part 1, disc-shaped portion 9' will be exposed to view when the article of clothing is being worn. Said disc-shaped portion 9' itself may be a decorative button or the like, or it may function to detachably accommodate a decorative button.

Figures 5 and 6 diagrammatically show a storage box 18 for main parts 8 of a button combination according to the invention.

As is shown in said figures, the box comprises a bottom 19 and a continuous upright wall 20, which comprises a thinner upper end for the purpose of placing a cover (not shown) thereon. Bottom 19 may project from circular wall 20 at one end, as is shown in Figure 5, whereby said end is provided with a hole 21, which makes it possible to suspend the box from a post or the like.

One or more projections 22, six in the illustrated embodiment, which are substantially circular in section, are provided in the interior of the box, each of said projections being provided with a projecting rib 23 on one side, in such a manner that ribs 23 are in line. The shape and the dimension of projection 22 largely corresponds with the shape and the dimension of central portion 5 of the above-described connecting piece 4, whilst ribs 23 correspond with a rib 6 and a rib 7 respectively as regards their shape and dimension. It will be apparent, that the above-described main parts 8 can thus be slid onto connecting pieces 22, 23 present on the bottom 19 of storage box 18 in a simple manner.

CLAIMS.

1. A button combination comprising a base part to be attached to an article of clothing and a main part to be detachably connected to said base part, characterized in that the main part is provided with two disc-shaped portions extending parallel to each other, which disc-shaped portions are interconnected near their circumference over part thereof, wherein a recess is provided in one of said disc-shaped portions, which recess is open at an edge of the disc-shaped portion in question, whilst the base part comprises two parallel disc-shaped portions, which are interconnected by a connecting piece, all this in such a manner that in order to interconnect the base part and the main part, the connecting piece of the base part is inserted into the recess in the main part with a clamped fit, wherein one of the disc-shaped portions of the base part is positioned between the disc-shaped portions of the main part.
2. A button combination according to claim 1, characterized in that the connecting piece of said base part is comprised of a central portion having an at least substantially circular section and at least one rib extending radially with respect thereto.
3. A button combination according to claim 2, characterized in that said connecting piece comprises two ribs which are positioned diametrically opposite each other with respect to the central middle portion, and which extend radially outwards from said connecting piece.
4. A button combination according to claim 2 or 3, characterized in that a blind bore is provided in the centre of the central middle portion of the connecting piece.
5. A button combination according to any one of the preceding claims, characterized in that the recess in the disc-shaped portion of the main part gradually narrows from its end located at the circumference of the disc-shaped portion towards the centre of the disc-shaped portion in question, eventually blending into a portion whose shape is adapted to the central middle portion of the base part, whilst the end of the recess is formed by a portion which can receive a rib-shaped portion of the connecting piece.
6. A box for storing main parts of a button combination according to any one of the preceding claims, characterized in that said box comprises at least one projection, which fits in the recesses formed in the main parts with a close fit.




Fig. 1

2/3




Fig. 3




Fig. 2




Fig. 4




Fig. 5




Fig. 6

INTERNATIONAL SEARCH REPORT

Int'l. Application No

PCT/NL 98/00488

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 A44B1/32 A44B1/08 A44B7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 6 A44B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 794 257 A (A. BOROWIEC) 12 February 1936 see page 2, column 1, paragraph 4; figures 13,14 ---	1
A	US 2 815 554 A (C. R. PIEPER) 10 December 1957 see column 2, line 11 - column 3, line 25; figures 1-9 ---	1-3
A	US 5 566 430 A (TUNG-TAI CHENG) 22 October 1996 see column 2, line 29 - column 3, line 9; figures 1-16 --- -/--	1

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

3 December 1998

Date of mailing of the international search report

15/12/1998

Name and mailing address of the ISA
 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Garnier, F

INTERNATIONAL SEARCH REPORT

International Application No

PCT/NL 98/00488

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 2 015 559 A (W.W.HOLM) 24 September 1935 see page 1, column 1, line 47 - page 2, column 1, line 45; figures 1-8 -----</p>	1

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/NL 98/00488

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR 794257 A	11-02-1936	NONE	
US 2815554 A	10-12-1957	NONE	
US 5566430 A	22-10-1996	NONE	
US 2015559 A	24-09-1935	NONE	